

# cmt

technology

## LX-1000



### Main Play Specification (15inch)

M a i n  B o a r d	Chip set	Onboard Intel Bay Trail J1900 Quad-Core 2.0GHz ,Turbo to 2.42GHz		
	Memory	1×SO-DIMM slot,Support DDR3 1066/1333/1600Max. capacity of system memory up 8GB		
	Storage	1×SATA. 1× mSATA		
	Display	VGA+LVDS VGA+HDMI HDMI+LVDS		
	Audio	Realtek ALC662		
	LAN	1×Realtek RTL8111F 1×MINI PCI-E slot, support WIFI/ 3G		
	SIO	ITE8786		
	I n t e r f a c e T y p e	COM	6×COM RS232 (COM2, 3 for +5V/+12V) COM2 support for RS485	
		USB	1×USB3.0 7× USB 2.0	
		GPIO	8bit GPIO	INTERNAL OPTION
Audio		Audio Out/Line in (SPK 2W, 80hm * 2)	INTERNAL OPTION	
Power Type		DC 12V DC 12V (RJ11) 1*CPU FAN, 1× SYS Fan connector		
Display	LCD	15" LED Back-light 1024*768 TFT LCD LQ150X1LW94		
	Touch	Capacitance touch,flat touch	TOUCH CONTROLLER	
	Double	12" 800*600 LCD		
Storage	SSD	64GB SSD (MSATA)		
SDRAM	DDR3	4GB DDR3 (CONNECTOR)		
	F_PANEL1	LAN LED		
MSR		Comply with ISO 7811	Option	
IC Card Reader		EMV Level 1	Option	
Power	SMPS	AC 220V 60Hz In/DC12V 7A Out		
Form	Size (L×W)	360mm*275mm		
OS Support		POS Ready 7		
Cooling Mode		Used cooling fan		