

UHF Mid-range Integrative Reader

Round
Polarization

Reading
Range > 6m



Brief Introduction

The products can be compatible with multi-protocol, small volume, quickly read, round-polar antenna is no limited of direction for tag, proof-water, can be used widely in RFID systems, the mainly applying site is:

1. Logistics and warehouse Management: Goods flow, warehouse management, and the flowing management of mail, parcel, luggage;
2. Intelligent parking Management: Parking management and automatic charge;
3. Productive lines Management: Production process fixed identification;
4. Product counterfeit-proof inspection: Using memory's write-protect functions inside tags, and identifying with true-false of products;
5. Other fields: Used widely in club management, library, student's school, consumption management, time management, dinner management, pool management

Technical parameters

Model	HYR6021A
Protocol	ISO18000-6B, ISO18000-6C (EPC GEN2)
工作频率	Standard ISM 902~928MHz and ISM 865~868MHz, other frequency available
Operation Mode	FHSS
RF Power	0~30dBm, software programmable
Reading Speed	Software Programmable, Average Reading per 64Bits: <6ms
Reading Mode	Timing or Touch, Software Programmable
Data Ports	Standard Wiegand26/34, RS485, RS232; software programmable WIFIport (order in advance), RJ45,
Data Input Port	Trigger input one team
Reading Range	More then 6 m
Reading Clue	Buzzer and LED
Antenna	Built-in round polarization antenna, Gain 7dBi
Power Supply	DC+9V direct current power(power adapter)
Dimension	240mm×240mm×30mm
Weight	1 Kg
Operation Temp	-20℃~+80℃